



SA-TP-2433

SINGLE AXLE TELESCOPING POLE TRAILER



Proudly Made in the U.S.A.



Boss Products, Inc.
602 Maple Lane
Wakarusa, Indiana 46573
Office: 574-970-0450

sales@bossproductsinc.com
www.PoleCatTrailers.com

TRAILER SPECIFICATIONS

GVWR	15,000 lbs./6,804 kg
Frame Construction	Steel Tube
Trailer Weight	3,720 lbs./1,687 kg
Trailer Width	8 ft. 1-31/32"
Trailer Length	24 ft.
Extended Length	33 ft.
Telescoping Tongue Max Extension	9 ft. (3 position)
Tire Sizes	215/75R17.5
Wheels per Axle	4
GAWR	15,000 lbs.
Suspension	Leaf-Spring (Overslung/Underslung)
Towing Electrical Plug	7-way Round Pin Plug
Brake System	Electric with Breakaway Kit
Lighting	US DOT Regulation LED
Color	Plascoat® White Finish

ACCESSORIES

Wheel Chocks	2
Clevis Hooks on Safety Chains	3/8 in.
Lunette Ring (with 4 mounting height locations)	3 in. I.D.
Square Sidewind Hitch Jack	12,000 lbs/5,443 kg. 26 in. lift
Moveable Stanchions with Locking Pins	6
Document Holder	1
Tightening Bar	1
Mud Flaps	Dual Wheel
Lashing Wenches with 5,400 lbs. Rate Straps	3

OPTIONS

Tool Boxes

Stainless Steel Front—Tool Boxes (2) 24 in. W x 14 in. H x 16 in. D

