



SSA - 11

SPLIT SINGLE AXLE REEL TRAILER



Boss Products, Inc.
602 Maple Lane
Wakarusa, IN 46573
Office: 574-970-0450

sales@bossproductsinc.com
www.PoleCatTrailers.com



TRAILER SPECIFICATIONS

GVWR	10,000 lbs. / 4,536 kg
Frame Construction	Steel Tube
Trailer Weight	2,100 lbs. / 953 kg
Trailer Width	102 in.
Trailer Length	11 ft.
Tire Sizes	235 / 75R17.5
Axle Wheels	2
GAWR	10,000 lbs. Split Axle
Suspension	None
Towing Electrical Plug	7 Way Round Pin
Brake System	Electric incl. Breakaway Kit, Battery & Charger
Lighting	US DOT Regulation LED
Color	Plascoat® White Finish

ACCESSORIES

Wheel Chocks	2
Clevis Hooks on Safety Chains	3/8 in.
Lunette Ring (with 4 mounting height locations)	3 in. I.D.
Square Sidewind Hitch Jack	12,000 lbs. with 26 in. Lift
Document Holder	1
Mud Flaps	Single Wheel
Anti-Spin Transportation Chain	1

REEL SPECIFICATIONS

Max Reel Width	60 in.
Max Reel Diameter	108 in. / 120 in. with reel inches off ground
Max Reel Lifting Weight	7,900 lbs. (3,583 kg)
2.875 in. Solid Cold Rolled Steel Shaft with (2) 12 in. Locking Reel Collars	1
Manual Prince Hydraulic Pump	1 Gallon Reservoir and 3000 PSI Capacity
Reel Lift Travel	19.375 in.

OPTIONS

12,000 lbs. Axle (no suspension)	Upgrade from 10,000 lbs. axle
----------------------------------	-------------------------------