



TAU - 1825

TANDEM AXLE TELESCOPING UTILITY TRAILER



Boss Products, Inc.
602 Maple Lane
Wakarusa, IN 46573
Office: 574-970-0450

sales@bossproductsinc.com
www.PoleCatTrailers.com

TRAILER SPECIFICATIONS

GVWR	12,000 lbs. / 5,443 kg
Frame Construction	Steel Tube
Trailer Weight	3,600 lbs. / 1,633 kg
Trailer Width	97 in.
Trailer Length	18.5 ft.
Extended Length	25 ft.
Trailer Bed Dimensions	106 in. L x 58 in. W x 15 in. H
Telescoping Tongue Max Extension	6 ft. -5 in.
Tire Sizes	235 / 80R16
Axle Wheels	4
GAWR	6,000 lbs. Tandem Underslung
Suspension	Leaf-Spring
Towing Electrical Plug	7 Way Round Pin
Brake System	Electric incl. Breakaway Kit, Battery & Charger
Lighting	US DOT Regulation LED
Color	Plascoat® White Finish
Tailgate	Fold Down

ACCESSORIES

Wheel Chocks	2
Clevis Hooks on Safety Chains	3/8 in.
Lunette Ring (with 4 mounting height locations)	2.5 in. I.D.
14 in. Utility Table Extension (for extra long pieces)	2
Square Sidewind Hitch Jack	12,000 lbs. with 26 in. Lift
Stainless Steel Front - Tool Boxes	(2) 24 in. W x 14 in. H x 16 in. D
Document Holder	1
Tightening Bar	1
Mud Flaps	Single Wheel
Workbenches	2 (1 on each side)
Slide Out Drawers	3
Removeable Utility Rack Posts with Locking Pins	1

REEL SPECIFICATIONS

Lashing Wenchers with 5,400 lbs. Rated Straps	3
---	---

OPTIONS

Reel Carrier	1
Heavy Duty Reel Carriers with (2) Locking Reel Collars	x
2.875 in. Solid Cold Rolled Steel Shaft with Brake Shaft Collar and Locking Reel Collar	x
48 in. Max Reel Width	x
72 in. Max Reel Diameter	x
Powder Coated Plascoat White	x
Brake Assembly	1
8 in. Overspin Brake with Bracket and Hardware	x
Mat Rack	1
Made of 1 in. x 1 in. x 0.125 in. Wall Square Steel Tube	x
96 ft. L x 38 in. W x 4 in. H	x
Powder Coated Textured Black	x
16 in. Ventilated Bronze Over Spin Brake Assembly	1